EUROPEAN PATENT APPLICATION

(43) Date of publication: 15.12.1999 Bulletin 1999/50

(51) Int Cl.6: **F16F 1/376**

(21) Application number: 99201547.9

(22) Date of filing: 18.05.1999

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU

MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 20.05.1998 IT TO980093 U

(71) Applicant: GATE S.p.A. 10123 Torino (IT)


(72) Inventor: Gabbin, Giuliano 14037 Portacomaro (Asti) (IT)

(74) Representative: Serra, Francesco et al c/o JACOBACCI & PERANI S.p.A.
Corso Regio Parco, 27
10152 Torino (IT)

(54) Vibration damper block

(57) An anti-vibration block is described comprising two substantially cylindrical coaxial end parts (4,6) joined together by a cylindrical body (7) coaxial with the end parts (4,6) and of smaller section than these, the said end parts (4,6) and the said cylindrical body (7) de-

fining a groove (10), a substantially cylindrical axial through-hole (11) passing through the block (2), the end parts (4,6) having on their outer faces opposite the groove (10) pairs of projections (12;14,16, 18) of I and T-shape respectively.



Description

[0001] The present invention relates to a vibration damper block, more precisely a vibration damper block for use on motor vehicles.

[0002] Problems of induced vibration exist, for example, in the region where the cooling radiator of the engine is fixed to the air duct coming from the fan or fans, and also where the fan unit is fixed to a duct.

[0003] The object of the present invention is that of providing a damper block or grommet which allows a drastic reduction of the vibrations generated or transmitted by members such as, for example, cooling fans, radiators or air ducts to be obtained, which is easy to construct and of low cost.

[0004] The present invention achieves the abovestated objects by a vibration damper block formed in rubber or plastics having the characteristics specifically set out in the following claims.

[0005] The invention will now be described with reference to the attached drawings, provided purely by way of non-limitative example, in which:

Figure 1 is a perspective view of a damper block according to the invention;

Figure 2 is a plan view of the block of Figure 1; Figure 3 is a view in section taken on the line III-III of Figure 2; and

Figure 4 illustrates the positioning of the damper block according to the invention in a fan unit.

[0006] Referring now to the drawings, where the same or corresponding parts are indicated with the same reference numerals, the vibration damper block according to the invention is generally indicated 2. The block 2 is made of rubber or plastics.

[0007] The block 2 comprises two end parts 4,6 of cylindrical form, joined together by a cylindrical body 7 of smaller section than that of the two end parts 4 and 6, creating a groove 10 between them.

[0008] A substantially cylindrical through-hole 11 passes through the block 2; the end parts 4, 6 carry on their outer faces opposite the groove 10 a pair of projections 12 of substantially I-shape and three pairs of projections 14, 16, 18 of substantially T-shape, with enlarged mushroom heads 19 at their ends facing towards the periphery of the end parts 4, 6.

[0009] The projections of each pair of projections 12, 14, 16, 18 are diametrically opposite one another such that the pairs of projections 12, 14, 16, 18 are equally angularly spaced by about 45°.

[0010] The ends of the projections of the pairs 12, 14, 16, 18 facing the periphery of the end parts 4, 6 are curved with the same radius of curvature as the end parts 4 and 6, whilst the opposite ends are curved and 55 projecting into the through-hole 11.

[0011] Making specific reference to Figure 4, in use a pair of damper blocks 2 according to the invention are

introduced into holes or eyes 20 formed in fixing tabs 22 of a fan unit 40 which, purely by way of non-limitative example, is shown with two cooling fans 42 and 44, in such a way that the groove 10 cooperates with the holes 20 so that the two end parts 4 and 6 are in contact with opposite sides of the fixing tab 22.

[0012] Once the blocks 2 are inserted into the holes 20 of the fixing tabs 22 of the fan unit 40 this can be fixed in a manner known per se to an air duct or a radiator (not shown).

[0013] Spacers 60, for example of metal, can be prearranged in the holes 20 to encourage correct positioning of the blocks 2.

[0014] Naturally, the principle of the invention remaining the same, the details of construction and the embodiments can be widely varied with respect to what has been described and illustrated, without by this departing from the ambit of the present invention.

Claims

20

25

30

- 1. A vibration damper block (2) formed of plastics or rubber, characterised in that it comprises two substantially coaxial end parts (4,6) joined together by a cylindrical body (7) coaxial with the end parts (4,6) and of smaller section than these, the said end parts (4,6) and the said cylindrical body (7) together defining a groove (10); a substantially cylindrical, axial through-hole (11) passing through the block (2), the end parts (4,6) having on their outer faces opposite the groove (10) a pair of projections (12) of substantially I-shape and a plurality of pairs of projections (14,16,18) of substantially T-shape with enlarged mushroom heads (19) at their ends facing towards the periphery of the end parts (4,6,) the projections of each pair of projections (12,14,16,18) being diametrically opposite one another.
- 40 2. A block according to Claim 1, characterised in that the said projections of each pair of projections (12,14,16,18) are equally angularly spaced.
 - 3. A block according to any preceding claim, characterised in that the ends of the projections of each pair of projections (12,14,16,18) facing towards the periphery of the ends parts (4,6) are curved with the same radius of curvature as the end parts (4,6).

2





FIG. 4





EUROPEAN SEARCH REPORT

Application Number

EP 99 20 1547

Category	Citation of document with indic	· · · · · · · · · · · · · · · · · · ·	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.8)	
Ą	PATENT ABSTRACTS OF J vol. 012, no. 257 (M- 20 July 1988 (1988-07 & JP 63 038732 A (KIN LTD), 19 February 198 * abstract *	719), -20) UGAWA RUBBER IND CO	1	F16F1/376	
<i>t</i>	EP 0 429 363 A (PAULS 29 May 1991 (1991-05- * abstract; figures *	1			
4	US 1 951 013 A (G.FLI 13 March 1934 (1934-0	013 A (G.FLINTERMANN) 1934 (1934-03-13)			
	US 2 353 952 A (F.L.Y 18 July 1944 (1944-07				
\	US 2 727 407 A (A.W.R 20 December 1955 (195				
A	FR 2 119 169 A (LEHR 4 August 1972 (1972-0	•		TECHNICAL FIELDS SEARCHED (Int.Cl.6)	
<u></u>	The present search report has be	en drawn up for all claims	_		
	Place of search	Date of completion of the search		Examiner	
	THE HAGUE	21 October 199	9 Pe	mberton, P	
X : pai Y : pai doc	CATEGORY OF CITED DOCUMENTS rticularly relevant if taken alone rticularly relevant if combined with anothe current of the same category chnological background	E : earlier paten after the filing D : document d L : document cit	ted in the application ted for other reason	blished on, or on	

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 99 20 1547

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-10-1999

Patent document cited in search repor	t	Publication date	Patent family member(s)	Publication date
JP 63038732	A	19-02-1988	NONE	
EP 0429363	A	29-05-1991	FR 2655109 A DE 69008677 D DE 69008677 T ES 2052214 T US 5123625 A	31-05-1991 09-06-1994 15-12-1994 01-07-1994 23-06-1992
US 1951013	A	13-03-1934	NONE	
US 2353952	A	18-07-1944	GB 575186 A	*
US 2727407	A	20-12-1955	NONE	
FR 2119169	A	04-08-1972	NONE	

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82